

GENERAL STATEMENTS

MK/X weighing hook is a self-powered electronic dynamometer making the device ideal for weight control at entry and exit of products, inventories, stock weighing, order checking, business deals...
MK/X has been designed to be hung from the bridge crane, hoist or crane. Optionally it can be supplied with infrared remot comand.

TECHNICAL CHARACTERISTICS

ON/OFF push button
CERO push button
TARA puch button (acumulative over 100% nominal load)
TARE erase
Automatic self-disconnection when very low battery.
Overload message.
Low battery message and indicator.
Battery tension indicator.
TARE indicator
CERO indicator
Weight unit indicator (kg, tn ó lb)
80h battery autonomy, charge in 8-14h.
IP-54 steel protection case.
LCD display with 4 digits 1".
Elevation accessories: 1 ring, 2 shackles and one revolving hook.
Breaking strength > 500% nominal capacity.
Accuracy class III (3.000 divisions).
Feed: rechargeable battery.
Working temperature -10°C +40°C.

OPTIONALS

Infrared remot comand having the following functions: added memory of partial weights total, memory reset and the other basic functions. Max. distance 30m.
Max pic indicator.
Transmission via radio to Motorman displays.
Load limiter or release by relay of already established load.
RS232 output for PC.
Foundry protection.

WEIGHING HOOK MODEL MK/X



DIMENSIONS:

| Model capacity Portée type | Division Échelon (Kg) | Dimensions (mm) | | | | | | Total Weight Poids Total (kg) | |
|----------------------------------|-----------------------------|-----------------|----------------|----------------|----------------|----|----|-------------------------------------|----------------------|
| | | L ₁ | L ₂ | L ₃ | L ₄ | A | B | Without Sans acc. | With Avec acc. |
| 200 | 0,1 | 114 | 224 | 484 | 359 | 17 | 19 | 3 | 4,7 |
| 500 | 0,2 | 114 | 224 | 484 | 359 | 17 | 19 | 3 | 4,7 |
| 1.000 | 0,5 | 114 | 224 | 529 | 379 | 17 | 19 | 3 | 5 |
| 2.000 | 1 | 114 | 224 | 529 | 379 | 17 | 19 | 3 | 5 |
| 3.000 | 1 | 132 | 322 | 692 | 512 | 23 | 30 | 3,9 | 7,3 |
| 5.000 | 2 | 132 | 322 | 692 | 512 | 23 | 30 | 4,6 | 9,9 |
| 6.000 | 2 | 141 | 322 | 692 | 566 | 26 | 35 | 5,2 | 15,8 |
| 10.000 | 5 | 150 | 425 | 925 | 700 | 33 | 43 | 6,2 | 23 |

